

# Standard Core Dimensions & Specifications

Semiconductor Noise Protection Choke

## » AMB Series Bead

Part No.	Finished Core (mm) <sup>1)</sup>			L <sub>eff</sub> <sup>2)</sup> (mm)	A <sub>eff</sub> <sup>3)</sup> (mm <sup>2</sup> )	2Φ <sub>m</sub> <sup>4)</sup> (μWb)	A <sub>L</sub> <sup>5)</sup> (μH)	Insulating cover
	OD	ID	HT					
AMB-03A-N	4.0	1.6	4.5	7.7	1.20	0.9	3.0	
AMB-03S-N	4.0	1.6	6.0	7.7	1.80	1.3	5.0	blue class
AMB-04S-N	5.0	1.6	6.0	9.1	3.60	2.7	9.0	resin
AMB-04B-N	5.0	1.6	7.5	9.1	4.80	3.6	12.0	
AMB-045A-N	6.5	2.4	6.0	13.3	0.6	0.6	0.86	

Notes :

- 1) The finished core dimensions shows a limiting ones.
- 2) Nominal values of magnetic path length.
- 3) Nominal values of cross-section area.
- 4) Minimum value at 50kHz, 80 A/m, RT(~25°C).
- 5) Normalized inductance, Minimum value at kHz with the oscillation voltage of 1V, RT(~25°C)
- 6) Minimum value at 50kHz with the oscillating voltage of 1V, 1turn, RT(~25°C).

## » AMK Series Spike Killer

Part Number	Finishd Core (mm) <sup>1)</sup>			L <sub>eff</sub> <sup>2)</sup> (mm)	A <sub>eff</sub> <sup>3)</sup> (mm <sup>2</sup> )	V <sub>eff</sub> <sup>4)</sup> (mm <sup>3</sup> )	W <sub>a</sub> <sup>5)</sup> (mm <sup>2</sup> )	A <sub>L</sub> <sup>6)</sup> (μH)	2Φ <sub>m</sub> <sup>7)</sup> (μWb)
	OD	ID	HT						
AMK-09S-N	10.7	5.5	6.3	25.0	3.5	88	24	1.8	3.9
AMK-10S-N	11.9	5.8	6.3	27.0	4.7	129	26	2.2	5.3
AMK-12A-N	14.0	6.6	4.8	31.0	4.7	147	34	1.9	5.2
AMK-12S-N	14.0	6.6	6.3	31.0	7.0	221	34	2.8	7.9
AMK-14S-N	15.9	6.8	6.5	34.3	10.0	350	36	3.7	11.2
AMK-15A-N	16.7	10.5	6.3	42.2	5.3	223	87	1.6	5.9
AMK-15S-N	16.9	8.6	6.5	38.7	8.8	345	59	2.8	9.8
AMK-18S-N	19.8	10.4	6.4	46.5	10.5	496	85	2.8	11.8
AMK-21S-N	22.8	12.4	6.3	54.2	12.3	675	121	2.8	13.8

Notes :

- 1) The finished core dimensions shows a nominal ones. Please consult sales department for tolerance.
- 2) Nominal values of magnetic path length.
- 3) Nominal values of cross-section area.
- 4) Nominal values of volume.
- 5) Nominal values of window area.
- 6) Normalized inductance, Minimum value at kHz with the oscillation voltage of 1V, RT(~25°C)
- 7) Total flux with its tolerances of ±15%. All values are measured at 50kHz, 80 A/m, RT(~25°C)